

## Topcoat Hygiene

### 3-4mm Anti-Slip Epoxy Screed with Decorative Flake..

Topcoat Hygiene is specially designed for use in commercial food preparation and storage areas. It is a seamless hygienic epoxy self levelling screed with an anti-slip textured finish. The system can be coved to wall-floor joint to provide an easy clean floor.

#### APPLICATIONS

Kitchens, Canteens, Toilets, Locker Rooms, Hospitals, Food Processing, Retail Areas etc.

#### SURFACE PREPARATION

The surface should be free of grease, fat, laitance, loose materials, dust and release agents. These contaminants can be removed by washing with an industrial detergent followed by dust free shot blasting or diamond grinding.

#### MIXING INSTRUCTIONS

Mix thoroughly, the resin and hardener together until colour is uniform. Continue mixing for a further two minutes. Paddle mixer is preferred.

#### COVERAGE

One coat is sufficient for light traffic areas. Where the concrete is rough or in medium traffic areas a second coat is recommended. One 10kg. unit will cover approx 50 m<sup>2</sup> depending on surface conditions.

#### HEALTH & SAFETY

Skin and eye contact should be avoided by use of suitable protective clothing such as gloves, goggles, apron etc. Use in well ventilated area. In the event of eye contact flush with water for 15 minutes and seek medical attention.

#### TECHNICAL DATA

Standard Colours	Battleship Grey, Gunmetal Grey, Sand Yellow, Honey Yellow, Tile Red, Tomato Red, Marine Blue, Sky Blue, Leaf Green.
------------------	--

Volume Solids	100%
---------------	------

Pot Life @ 25 <sup>0</sup> C	30 min
------------------------------	--------

Packaging	10 Kg.
-----------	--------

#### Mixing Ratio

Volume-Resin: Hardener	3 :1
------------------------	------

Weight- Resin; Hardener	4:1
-------------------------	-----

Shelf life <small>(sealed original container)</small>	12 months.
--	------------

Storage Conditions	5 - 40 <sup>0</sup> C
--------------------	-----------------------

Application temperature	12 <sup>0</sup> C - 35 <sup>0</sup> C
-------------------------	---------------------------------------

Service Time - Foot Traffic	24 Hours
-----------------------------	----------

Recoat time	24 hours
-------------	----------

Conforms to British Slip Resistance Standard  
No. BS903: Part A26.