



## Topcoat Pebble Decorative Internal/External Stone Finish

Topcoat Pebble system is a hard wearing decorative resin floor screed suitable for indoor and outdoor applications. It comes in a range of natural stone and coloured stone anti-slip floor finishes.

### APPLICATIONS

Highways – Bus lanes, Ramp approach areas.  
Walkways – Stairways, Pedestrian bridges,  
Wheelchair ramps, Apartment balconies and  
Access paths.  
Car Parks – Access ramps, Barrier approaches.

### SURFACE PREPARATION

The surface should be free of grease, fat, laitance, loose materials, dust and release agents. These contaminants can be removed by washing with an industrial detergent followed by dust free shot blasting or diamond grinding.

### MIXING INSTRUCTIONS

Mix thoroughly, the resin and hardener together until colour is uniform. Continue mixing for a further two minutes. Paddle mixer is preferred.

### HEALTH & SAFETY

Skin and eye contact should be avoided by use of suitable protective clothing such as gloves, goggles, apron etc. Use in well ventilated area. In the event of eye contact flush with water for 15 minutes and seek medical attention.

### TECHNICAL DATA

Stone Finishes	Golden Pea, Granite, Chinese Bauxite and Coloured (Yellow, Red, Green, Blue, Jade).
Stone Sizes	0.9–1.4 mm Foot Grade 1.0-3.0 mm Traffic Grade
Volume Solids	100%
Pot Life @ 25 <sup>0</sup> C	30 min
Packaging	25 Kg.
Mixing Ratio	
Volume-Resin: Hardener	3 :1
Weight- Resin; Hardener	4:1
Shelf life (sealed original container)	12 months.
Storage Conditions	5 - 30 <sup>0</sup> C
Application temperature	12 <sup>0</sup> C - 30 <sup>0</sup> C
Service Time - Foot Traffic	24 Hours